

Inductive Sensors



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
18 mm - Embeddable, <i>microfast</i>® Connection 	Bi 5U-G18-ADZ30X2-B3331	M4281213	<i>Uprox</i>	5	2-Wire AC/DC Short-Circuit Protected
	Bi 5-G18-ADZ30X2-B3331	T4208092		5	
	Bi 8-G18-ADZ30X2-B3331	T4209301	<i>Ext. Range</i>	8	
18 mm - Embeddable, <i>microfast</i> Connection, Teflon Coated 	Bi 5-GT18-ADZ30X2-B3331	T4255491		5	2-Wire AC/DC Short-Circuit Protected
	Bi 5-GT18-ADZ30X2-B3331/S34	T4255400	<i>WFI</i>	5	
	Bi 5-GT18H-ADZ30X2-B3331/S34	T4255289	<i>WFI</i>	5	
	Bi 5-GT18H-ADZ30X2-B3331/S34/S1589	T4255283	<i>weldguard</i> ®	5	
	Bi 5U-GT18-ADZ30X2-B3331	M4281223	<i>Uprox</i>	5	
18 mm - Embeddable, <i>microfast</i> Connection 	Bi 5-G18-AZ3X-B3331	T4372098		5	2-Wire AC/DC

For detailed sensor specifications see Section M.
Normally Closed versions available upon request, consult factory.



Output	Switching Freq. (Hz)	Operating Current (mA) VAC/VDC	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cordset	Wiring Diagram #	Wiring Diagrams
20-250 VAC 10-300 VDC	20	≤400/300	-30 to +85	IP 67	CPB	PA 12	GN	YE	KB 3T-*	1	<p>Diagram 1</p>
	20	≤400/300	-25 to +70	IP 67	CPB	PA 12	GN	RD	KB 3T-*	1	
	20	≤400/300	-25 to +70	IP 67	SS	PA 12	GN	RD	KB 3T-*	1	
20-250 VAC 10-300 VDC	20	≤400/300	-25 to +70	IP 67	TC	TC	GN	RD	KB 3T-*	1	
	20	≤400/300	-25 to +70	IP 67	TC	TC	GN	RD	KB 3T-*	1	
	20	≤400/300	-25 to +70	IP 67	TC	SF	GN	RD	KB 3T-*	1	
	20	≤400/300	-25 to +70	IP 67	TC	WG	GN	RD	KBE 3T-*	1	
	20	≤400/300	-30 to +85	IP 67	TC	TC	GN	YE	KB 3T-*	1	
20-250 VAC 10-300 VDC	20	≤400/300	-25 to +70	IP 67	CPB	PA 12	N/A	RD	KB 3T-*	1	

Barrels

* Length in meters.

For material descriptions see page M22.