

WIRING DIAGRAMS		LOCKNUT LN-M18		SPECIFICATIONS																																																					
<p>OUTPUT: AN6X</p>				<table border="1"> <tr><td>OPERATING VOLTAGE</td><td>10-30 VDC</td></tr> <tr><td>RIPPLE</td><td>≤10%</td></tr> <tr><td>DIFFERENTIAL TRAVEL (HYSTERESIS)</td><td>3-15% (5% TYPICAL)</td></tr> <tr><td>VOLTAGE DROP ACROSS CONDUCTING SENSOR</td><td>≤1.8 V at 200 mA</td></tr> <tr><td>OUTPUT FUNCTION</td><td>NORMALLY OPEN 3-WIRE DC SELF-CONTAINED</td></tr> <tr><td>TTL COMPATIBLE</td><td>NO</td></tr> <tr><td>SHORT-CIRCUIT PROTECTED</td><td>YES</td></tr> <tr><td>TRIGGER CURRENT FOR OVERLOAD PROTECTION</td><td>≥220 mA</td></tr> <tr><td>CONTINUOUS LOAD CURRENT</td><td>≤200 mA</td></tr> <tr><td>OFF-STATE (LEAKAGE) CURRENT</td><td><10 μA</td></tr> <tr><td>NO-LOAD CURRENT</td><td>5.5-9.5 mA</td></tr> <tr><td>TIME DELAY BEFORE AVAILABILITY</td><td>≤8 ms</td></tr> <tr><td>POWER-ON EFFECT PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>REVERSE POLARITY PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>WIRE-BREAK PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>PROTECTION AGAINST TRANSIENTS</td><td>EN 60947-5-2</td></tr> <tr><td>OPERATING TEMPERATURE</td><td>-25°C to +70°C (-13°F to +158°F)</td></tr> <tr><td>ENCLOSURE</td><td>MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67</td></tr> <tr><td>SHOCK</td><td>30 g, 11 ms</td></tr> <tr><td>VIBRATION</td><td>55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)</td></tr> <tr><td>LED FUNCTION</td><td>RED: OUTPUT ENERGIZED</td></tr> <tr><td>RATED OPERATING DISTANCE(Sn)</td><td>5 mm = .197" (NOMINAL)</td></tr> <tr><td>SWITCHING FREQUENCY</td><td>1000 Hz</td></tr> <tr><td>REPEATABILITY</td><td>≤2% of RATED OPERATING DISTANCE</td></tr> <tr><td>EMBEDDABLE (SHIELDED)</td><td>YES</td></tr> <tr><td>MATING PLUGS & CABLES</td><td>4-PIN "MINIFAST" CONSTRUCTION</td></tr> </table>		OPERATING VOLTAGE	10-30 VDC	RIPPLE	≤10%	DIFFERENTIAL TRAVEL (HYSTERESIS)	3-15% (5% TYPICAL)	VOLTAGE DROP ACROSS CONDUCTING SENSOR	≤1.8 V at 200 mA	OUTPUT FUNCTION	NORMALLY OPEN 3-WIRE DC SELF-CONTAINED	TTL COMPATIBLE	NO	SHORT-CIRCUIT PROTECTED	YES	TRIGGER CURRENT FOR OVERLOAD PROTECTION	≥220 mA	CONTINUOUS LOAD CURRENT	≤200 mA	OFF-STATE (LEAKAGE) CURRENT	<10 μA	NO-LOAD CURRENT	5.5-9.5 mA	TIME DELAY BEFORE AVAILABILITY	≤8 ms	POWER-ON EFFECT PROTECTION	INCORPORATED	REVERSE POLARITY PROTECTION	INCORPORATED	WIRE-BREAK PROTECTION	INCORPORATED	PROTECTION AGAINST TRANSIENTS	EN 60947-5-2	OPERATING TEMPERATURE	-25°C to +70°C (-13°F to +158°F)	ENCLOSURE	MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67	SHOCK	30 g, 11 ms	VIBRATION	55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)	LED FUNCTION	RED: OUTPUT ENERGIZED	RATED OPERATING DISTANCE(Sn)	5 mm = .197" (NOMINAL)	SWITCHING FREQUENCY	1000 Hz	REPEATABILITY	≤2% of RATED OPERATING DISTANCE	EMBEDDABLE (SHIELDED)	YES	MATING PLUGS & CABLES	4-PIN "MINIFAST" CONSTRUCTION
OPERATING VOLTAGE	10-30 VDC																																																								
RIPPLE	≤10%																																																								
DIFFERENTIAL TRAVEL (HYSTERESIS)	3-15% (5% TYPICAL)																																																								
VOLTAGE DROP ACROSS CONDUCTING SENSOR	≤1.8 V at 200 mA																																																								
OUTPUT FUNCTION	NORMALLY OPEN 3-WIRE DC SELF-CONTAINED																																																								
TTL COMPATIBLE	NO																																																								
SHORT-CIRCUIT PROTECTED	YES																																																								
TRIGGER CURRENT FOR OVERLOAD PROTECTION	≥220 mA																																																								
CONTINUOUS LOAD CURRENT	≤200 mA																																																								
OFF-STATE (LEAKAGE) CURRENT	<10 μA																																																								
NO-LOAD CURRENT	5.5-9.5 mA																																																								
TIME DELAY BEFORE AVAILABILITY	≤8 ms																																																								
POWER-ON EFFECT PROTECTION	INCORPORATED																																																								
REVERSE POLARITY PROTECTION	INCORPORATED																																																								
WIRE-BREAK PROTECTION	INCORPORATED																																																								
PROTECTION AGAINST TRANSIENTS	EN 60947-5-2																																																								
OPERATING TEMPERATURE	-25°C to +70°C (-13°F to +158°F)																																																								
ENCLOSURE	MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67																																																								
SHOCK	30 g, 11 ms																																																								
VIBRATION	55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)																																																								
LED FUNCTION	RED: OUTPUT ENERGIZED																																																								
RATED OPERATING DISTANCE(Sn)	5 mm = .197" (NOMINAL)																																																								
SWITCHING FREQUENCY	1000 Hz																																																								
REPEATABILITY	≤2% of RATED OPERATING DISTANCE																																																								
EMBEDDABLE (SHIELDED)	YES																																																								
MATING PLUGS & CABLES	4-PIN "MINIFAST" CONSTRUCTION																																																								
				<table border="1"> <tr> <td>MATERIAL</td> <td>BRASS BARREL</td> <td>3RD ANGLE PROJECTION</td> <td rowspan="2"> </td> <td colspan="2" rowspan="2"> TURCK INC 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 PHONE: (763) 553-7300 </td> </tr> <tr> <td>FINISH</td> <td>COPPER/NICKEL/ CHROME PLATING</td> <td></td> </tr> <tr> <td>DRFT</td> <td>SMW</td> <td>DATE</td> <td>10/22/86</td> <td colspan="2">PART NO./DESCR.</td> </tr> <tr> <td>DSGN</td> <td></td> <td>Y#</td> <td></td> <td colspan="2">Bi5-G18-AN6X-B1341</td> </tr> <tr> <td colspan="3">TMI</td> <td>SIZE</td> <td>ID NO.</td> <td>REV</td> </tr> <tr> <td colspan="3">DIMENSION UNITS: INCHES [MILLIMETERS]</td> <td>B</td> <td>4695200</td> <td>B</td> </tr> <tr> <td colspan="3"></td> <td>SCALE</td> <td>NONE</td> <td>BMQD-D\4695200</td> </tr> <tr> <td colspan="3"></td> <td></td> <td></td> <td>SHEET OF</td> </tr> </table>		MATERIAL	BRASS BARREL	3RD ANGLE PROJECTION		TURCK INC 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 PHONE: (763) 553-7300		FINISH	COPPER/NICKEL/ CHROME PLATING		DRFT	SMW	DATE	10/22/86	PART NO./DESCR.		DSGN		Y#		Bi5-G18-AN6X-B1341		TMI			SIZE	ID NO.	REV	DIMENSION UNITS: INCHES [MILLIMETERS]			B	4695200	B				SCALE	NONE	BMQD-D\4695200						SHEET OF							
MATERIAL	BRASS BARREL	3RD ANGLE PROJECTION		TURCK INC 3000 CAMPUS DRIVE MINNEAPOLIS, MN 55441 PHONE: (763) 553-7300																																																					
FINISH	COPPER/NICKEL/ CHROME PLATING																																																								
DRFT	SMW	DATE	10/22/86	PART NO./DESCR.																																																					
DSGN		Y#		Bi5-G18-AN6X-B1341																																																					
TMI			SIZE	ID NO.	REV																																																				
DIMENSION UNITS: INCHES [MILLIMETERS]			B	4695200	B																																																				
			SCALE	NONE	BMQD-D\4695200																																																				
					SHEET OF																																																				
<p>SHORT-CIRCUIT AND OVERLOAD PROTECTED</p>																																																									
<p>REVISIONS</p>																																																									
B	SEE REVISION DOCUMENT G18ANP34	GMB	6/21/90																																																						
REV	DESCRIPTION	DRFT	DATE	ECO NO.																																																					