

WIRING DIAGRAMS		LOCKNUT LN-P30		SPECIFICATIONS																																																									
<p>OUTPUT: AN6X</p>				<table border="1"> <tr><td>OPERATING VOLTAGE</td><td>10-30 VDC</td></tr> <tr><td>RIPPLE</td><td>≤10%</td></tr> <tr><td>HYSTERESIS (DIFFERENTIAL TRAVEL)</td><td>3-15% (5% TYPICAL)</td></tr> <tr><td>VOLTAGE DROP ACROSS CONDUCTING SENSOR</td><td>≤1.8 V at 200 mA</td></tr> <tr><td>OUTPUT FUNCTION</td><td>NORMALLY OPEN 3-WIRE DC SELF-CONTAINED</td></tr> <tr><td>TTL COMPATIBLE</td><td>NO</td></tr> <tr><td>SHORT-CIRCUIT PROTECTED</td><td>YES</td></tr> <tr><td>TRIGGER CURRENT FOR OVERLOAD PROTECTION</td><td>≥220 mA</td></tr> <tr><td>CONTINUOUS LOAD CURRENT</td><td>≤200 mA</td></tr> <tr><td>LEAKAGE (OFF-STATE) CURRENT</td><td><10 μA</td></tr> <tr><td>NO-LOAD CURRENT</td><td>5.5-9.5 mA</td></tr> <tr><td>TIME DELAY BEFORE AVAILABILITY</td><td>≤8 ms</td></tr> <tr><td>POWER-ON EFFECT PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>POLARITY INVERSION PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>WIRE BREAK PROTECTION</td><td>INCORPORATED</td></tr> <tr><td>PROTECTION AGAINST TRANSIENTS</td><td>2 kV, 1 ms, 1 kΩ</td></tr> <tr><td>OPERATING TEMPERATURE</td><td>-25°C to +70°C (-13°F to +158°F)</td></tr> <tr><td>ENCLOSURE</td><td>MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67</td></tr> <tr><td>SHOCK</td><td>30 g, 11 ms</td></tr> <tr><td>VIBRATION</td><td>55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)</td></tr> <tr><td>LED FUNCTION</td><td>RED: OUTPUT ENERGIZED</td></tr> <tr><td>SENSING RANGE</td><td>15 mm = .591" (NOMINAL)</td></tr> <tr><td>SWITCHING FREQUENCY</td><td>500 Hz</td></tr> <tr><td>REPEATABILITY</td><td>≤2% of NOMINAL SENSING RANGE</td></tr> <tr><td>SHIELDED</td><td>NO</td></tr> <tr><td>MATING PLUGS/CABLES</td><td>4-PIN "MINIFAST" CONSTRUCTION</td></tr> </table>		OPERATING VOLTAGE	10-30 VDC	RIPPLE	≤10%	HYSTERESIS (DIFFERENTIAL TRAVEL)	3-15% (5% TYPICAL)	VOLTAGE DROP ACROSS CONDUCTING SENSOR	≤1.8 V at 200 mA	OUTPUT FUNCTION	NORMALLY OPEN 3-WIRE DC SELF-CONTAINED	TTL COMPATIBLE	NO	SHORT-CIRCUIT PROTECTED	YES	TRIGGER CURRENT FOR OVERLOAD PROTECTION	≥220 mA	CONTINUOUS LOAD CURRENT	≤200 mA	LEAKAGE (OFF-STATE) CURRENT	<10 μA	NO-LOAD CURRENT	5.5-9.5 mA	TIME DELAY BEFORE AVAILABILITY	≤8 ms	POWER-ON EFFECT PROTECTION	INCORPORATED	POLARITY INVERSION PROTECTION	INCORPORATED	WIRE BREAK PROTECTION	INCORPORATED	PROTECTION AGAINST TRANSIENTS	2 kV, 1 ms, 1 kΩ	OPERATING TEMPERATURE	-25°C to +70°C (-13°F to +158°F)	ENCLOSURE	MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67	SHOCK	30 g, 11 ms	VIBRATION	55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)	LED FUNCTION	RED: OUTPUT ENERGIZED	SENSING RANGE	15 mm = .591" (NOMINAL)	SWITCHING FREQUENCY	500 Hz	REPEATABILITY	≤2% of NOMINAL SENSING RANGE	SHIELDED	NO	MATING PLUGS/CABLES	4-PIN "MINIFAST" CONSTRUCTION				
OPERATING VOLTAGE	10-30 VDC																																																												
RIPPLE	≤10%																																																												
HYSTERESIS (DIFFERENTIAL TRAVEL)	3-15% (5% TYPICAL)																																																												
VOLTAGE DROP ACROSS CONDUCTING SENSOR	≤1.8 V at 200 mA																																																												
OUTPUT FUNCTION	NORMALLY OPEN 3-WIRE DC SELF-CONTAINED																																																												
TTL COMPATIBLE	NO																																																												
SHORT-CIRCUIT PROTECTED	YES																																																												
TRIGGER CURRENT FOR OVERLOAD PROTECTION	≥220 mA																																																												
CONTINUOUS LOAD CURRENT	≤200 mA																																																												
LEAKAGE (OFF-STATE) CURRENT	<10 μA																																																												
NO-LOAD CURRENT	5.5-9.5 mA																																																												
TIME DELAY BEFORE AVAILABILITY	≤8 ms																																																												
POWER-ON EFFECT PROTECTION	INCORPORATED																																																												
POLARITY INVERSION PROTECTION	INCORPORATED																																																												
WIRE BREAK PROTECTION	INCORPORATED																																																												
PROTECTION AGAINST TRANSIENTS	2 kV, 1 ms, 1 kΩ																																																												
OPERATING TEMPERATURE	-25°C to +70°C (-13°F to +158°F)																																																												
ENCLOSURE	MEETS NEMA 1, 3, 4, 6, 13 AND IEC IP67																																																												
SHOCK	30 g, 11 ms																																																												
VIBRATION	55 Hz, 1 mm AMPLITUDE (IN ALL 3 PLANES)																																																												
LED FUNCTION	RED: OUTPUT ENERGIZED																																																												
SENSING RANGE	15 mm = .591" (NOMINAL)																																																												
SWITCHING FREQUENCY	500 Hz																																																												
REPEATABILITY	≤2% of NOMINAL SENSING RANGE																																																												
SHIELDED	NO																																																												
MATING PLUGS/CABLES	4-PIN "MINIFAST" CONSTRUCTION																																																												
		<table border="1"> <tr><td>MATERIAL</td><td>PA 12-GF30 PLASTIC BARREL</td><td colspan="2">3RD ANGLE PROJECTION</td><td colspan="2" rowspan="2"> </td></tr> <tr><td>FINISH</td><td></td><td colspan="2"></td></tr> <tr><td>DRWN</td><td>RJP</td><td>DATE</td><td>4/27/92</td><td colspan="2">PART NO.</td></tr> <tr><td>CHKD</td><td></td><td>DATE</td><td></td><td colspan="2">Ni15-P30-AN6X-B2141</td></tr> <tr><td>TMI</td><td></td><td></td><td></td><td>SIZE</td><td>ID NO.</td></tr> <tr><td></td><td></td><td></td><td></td><td>B</td><td>4697600</td></tr> <tr><td></td><td></td><td></td><td></td><td>SCALE</td><td>NONE</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td>BPQD-D\4697600</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td>SHEET</td></tr> <tr><td></td><td></td><td></td><td></td><td></td><td>OF</td></tr> </table>		MATERIAL	PA 12-GF30 PLASTIC BARREL	3RD ANGLE PROJECTION				FINISH				DRWN	RJP	DATE	4/27/92	PART NO.		CHKD		DATE		Ni15-P30-AN6X-B2141		TMI				SIZE	ID NO.					B	4697600					SCALE	NONE						BPQD-D\4697600						SHEET						OF
MATERIAL	PA 12-GF30 PLASTIC BARREL	3RD ANGLE PROJECTION																																																											
FINISH																																																													
DRWN	RJP	DATE	4/27/92	PART NO.																																																									
CHKD		DATE		Ni15-P30-AN6X-B2141																																																									
TMI				SIZE	ID NO.																																																								
				B	4697600																																																								
				SCALE	NONE																																																								
					BPQD-D\4697600																																																								
					SHEET																																																								
					OF																																																								
REV	DESCRIPTION	DRFT	DATE	CHKD																																																									
REVISIONS																																																													

TURCK INC
 3000 CAMPUS DRIVE
 MINNEAPOLIS, MN 55441
 PHONE: (612) 553-9224